D237

# D237

# Bronze Gate Valve with Lockshield



**PN20** 


## **Features & Benefits**

- · Crane gate valves offer the ultimate in dependable service wherever minimum pressure drop is important.
- The D237 carries the British Standards Institution Kitemark your assurance of exacting quality standards
- WRAS approved for use on wholesome (potable) water in sizes 1/2" - 2" only
- WRAS approval temperature 85°C max

### **Materials**

PART	MATERIAL	SIZES
Body	Bronze BS EN 1982 CC491K	<sup>1</sup> /2 - 3
Bonnet	Bronze BS EN 1982 CC491K	<sup>1</sup> /2 - 3
Disc	Bronze BS EN 1982 CC491K	<sup>1</sup> /2 - 3
Stem	DZR Brass BS EN 12164 CW602N	<sup>1</sup> /2 - 3
Stuffing Box	DZR Brass BS EN 12164 CW602N	2 <sup>1</sup> /2 & 3
Stem Retainer	DZR Brass BS EN 12164 CW602N	<sup>1</sup> /2 - 2
Gland	Brass BS EN 12164 CW614N	1 - 3
Packing	Asbestos Free	<sup>1</sup> /2 - 3
Lockshield	Brass BS EN 12164 CW614N	<sup>1</sup> /2 - 3
Box Spanner	Mild Steel	<sup>1</sup> /2 - 3

## **Dimensional Drawing**



# **Dimensions & Weights**

SIZE (inch)	WEIGHT (kg)	A (mm)	B (mm)	C (mm)	D (mm)
1/2	0.276	50	78	90	100
3 <sub>/4</sub>	0.389	54	87	90	100
1	0.593	62	106	125	100
1 <sup>1</sup> /4	0.831	71	116	125	100
1 <sup>1</sup> /2	1.248	77.5	132	125	100
2	1.882	87.5	156	125	100
2 <sup>1</sup> /2	4.15	96	218	-	-
3	6.24	105	253	-	-

### **Pressure/Temperature Ratings**

TEMPERATURE (°C)	-10 to 100	180
PRESSURE (BAR)	20	9

Intermediate pressure ratings shall be determined by interpolation.

#### PRESSURE RATING: PN20 **TEMPERATURE OPERATING RANGE:**

#### **OPERATOR:** Lockshield.

Gate valves are best for services that require infrequent valve operation, and where the disc is kept either fully opened or fully closed. They are not practical for throttling. **END CONNECTION:** Taper threaded to SPECIFICATION: Solid wedge disc, non-rising stem, screwed in bonnet. Valves are manufactured in BS EN 10226-2 (ISO 7-1) formerly BS 21 accordance with BS EN 12288: 2010 PN20 Series B and are BSI Kitemark approved. This valve is not suitable for use on group 1 gases or unstable fluids, as defined by the Pressure Equipment Directive 2014/68/EU.\* AVAILABLE OPTIONS: P103 lockshield key 1/2" - 2" P100 lockshield key 21/2" - 3"

\* See page 155 for more information

Valid as of 290719

-10 to 180°C

Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Crane Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.





85